Merhow's Bronco Series trailers provides a significant list of standard features for this economical choice. You may select from straight load or slant load in both bumper pull and gooseneck configurations.

- Warranty 8 Year Structural
- Height 7'6" Width: 7'0"
- Stall Size Width at Sidewall: 40", Diagonal Stall Length: 10'2"
- · Short Wall 4' GN
- Chassis Tubular Aluminum with Tongue and Groove Extruded Aluminum Floor
- Dividers Alum. Formed Tubular Dividers w/ Hands Free Slam Latches, Padded, Spring Loaded
- Rear Tack Collapsible Wall, Removable Saddle Tree, Blanket Bars, Brush Box, Bridle Hooks, and Light
- Roof One Piece Aluminum, Cast Aluminum Corner Caps with Horse Logo
- · Roof Bows Tubular Aluminum
- Rear Hoop Tubular Aluminum
- Rear Doors (2) Full Height Step-In Rear Doors, 20x20 Sliding Window w/ Screen and Bar Guards in Horse Door, Independent Two-Point Cam Latches.
- All Locks are Keyed Alike
- Escape Door Full Height and Width on Front of First Stall on 3
 Horse and Larger Units
- Axles Dexter Torsion Axles & Radial Tires
- Spare Tire Spare Tire and Wheel

- Brakes Electric Self Adjusting on all Wheels
- Coupler 2-5/16 Bulldog Top Latch BP, Slide Latch GN
- Jack Side Crank Moved to Rear of A-Frame BP
- Single Leg GN
- Skin White Baked-On-Enamel Aluminum fastened with 3M Tape
- Front Rock Guard on all Bumper Pulls
- Stall Area Walls Ballistic lined and insulated up 48" .100 aluminum kick wall on hip side of Slant Loads
- Rubber Mats
- (1) Two-way pop up roof vents per stall
- Extruded aluminum DDFD each stall (slant loads)
- · Hip windows with screen and bar guard
- (2) Exterior and interior horse ties per stall
- Electrical One L.E.D. Light per Horse Stall w/ Remote Switch
- All Exterior L.E.D. Lights
- LED Load Light
- · Sealed Beam Flush Mount LED Tail Lights
- · Dressing Room Rubber on floor
- Dome Light with Remote Switch
- 30x74 Dressing Room Door
- Drip Guard Above Dressing Room Door
- 2nd Location for Saddle Tree